

X1/Y2 SAFETY (S SERIES) NPO DIELECTRIC

| | | Tolerance | | 1808 | 1812 | 2211 |
|-----|--------|-----------|----|--------------------------|--------------------------|--------------------------|
| | | | | 3,000 Rated (VDC) | 3,000 Rated (VDC) | 3,000 Rated (VDC) |
| | | | | 5,000 Peak Impulse Surge | 5,000 Peak Impulse Surge | 5,000 Peak Impulse Surge |
| 4R0 | 4.0 pF | J K | GE | | | LB |
| 5R0 | 5.0 pF | | GE | | | LB |
| 100 | 10 pF | | GE | HB | | LB |
| 120 | 12 pF | | GE | HB | | LB |
| 150 | 15 pF | | GE | HB | | LB |
| 180 | 180 pF | | GE | HB | | LB |
| 220 | 220 pF | | GE | HB | | LB |
| 270 | 270 pF | | GE | HB | | LB |
| 330 | 330 pF | | GE | HB | | LB |
| 390 | 390 pF | | GF | HB | | LB |
| 470 | 470 pF | | GF | HB | | LB |
| 560 | 560 pF | | GF | HB | | LB |
| 680 | 680 pF | | GF | HB | | LB |
| 820 | 820 pF | | GF | HB | | LB |
| 101 | 100 pF | | GH | HB | | LB |
| 121 | 120 pF | | GH | HB | | LC |
| 151 | 150 pF | | GH | HB | | LC |
| 181 | 180 pF | | | HB | | LC |
| 221 | 220 pF | | | HC | | LC |
| 271 | 270 pF | | | HC | | LC |
| 331 | 330 pF | | HC | | LC | |
| 391 | 390 pF | | HC | | LC | |
| 471 | 470 pF | | HC | | LC | |
| 561 | 560 pF | | | | LC | |
| 681 | 680 pF | | | | LC | |

